

## Lifestyle ClimbMill

### TOUCH XL CONSOLE

C-LS-TOUCHXL

Created for low-volume facilities, our Lifestyle ClimbMill features a compact design that makes it possible to bring climbing workouts to facilities with lower ceilings. Smart features make workouts comfortable and secure, and our durable components will keep your people climbing for years. It's even as easy to service as it is to use, so it will always be ready.



WiFi-enabled Touch XL Console features an app-based interface that mirrors familiar smartphone and tablet operating systems, making it easy for members to connect to the content that keeps them moving.

**Note:** Products with Touch XL Console must be connected to a power source.



CONSOLE	
<b>DISPLAY</b>	56 cm / 22" class capacitive touchscreen LCD
<b>WORKOUTS</b>	Go, manual, Sprint 8†, Landmarks†, Virtual Active, target heart rate, interval training, fat burn, rolling hills, constant watts†, glute training†, goal training, fitness tests, custom  †Some of these programs may not be available on this frame.
<b>IFIT ON-DEMAND WORKOUTS</b>	Optional
<b>LANGUAGES</b>	English, German, French, Italian, Spanish, Dutch, Portuguese, Chinese-S, Chinese-T, Japanese, Korean, Swedish, Finnish, Russian, Arabic, Turkish, Polish, Welsh, Basque, Vietnamese, Somali, Danish, Thai, Malay, Catalan
<b>FAN</b>	Yes
<b>ANALOG TV</b>	NTSC, PAL, SECAM
<b>DIGITAL TV</b>	ATSC 1.0, QAM-B, ISDB-T, ISDB-Tb, DVB-C/C2/S/S2/T/T2
<b>IPTV</b>	Content: MPEG2/H262, AVC/H264 Protocols: UDP, RTSP, HTTP, HTTPS
<b>WIFI</b>	Yes
<b>BLUETOOTH</b>	Yes; smartphones, headphones, heart rate
<b>RFID WIRELESS LOGIN</b>	Yes
<b>CONNECTS TO APPLE WATCH</b>	Yes
<b>MADE FOR IPHONE, IPAD, IPOD</b>	Yes
<b>CONNECTS TO SAMSUNG GALAXY WATCH</b>	Yes

<b>USB PORT</b>	Yes
<b>WIRELESS CHARGING (QI)</b>	Yes
<b>CSAFE READY</b>	Yes
<b>AUTO WAKE-UP</b>	Yes
	Note: Products with Touch XL Console must be connected to a power source.
FRAME	
<b>POWER REQUIREMENTS</b>	100–240 V — 50/60Hz AC
<b>MINIMUM USER WEIGHT</b>	45 kg / 99 lbs.
<b>MAXIMUM USER WEIGHT</b>	136 kg / 300 lbs.
<b>LOCKING STAIRCASE</b>	Yes
<b>HANDLEBAR DESIGN</b>	Side
<b>CONTACT &amp; TELEMETRIC HR</b>	Yes
<b>DRIVE SYSTEM</b>	Clutched ECB with industrial-grade drive chain and belt
<b>ETHERNET CONNECTIVITY</b>	Yes
<b>CONTROL ZONE</b>	No
<b>ASSEMBLED DIMENSIONS</b>	160 x 72 x 208 cm / 63.1" x 28.2" x 81.7"
<b>SERVICE CASTER</b>	No
<b>STEP DIMENSIONS</b>	23 x 40.2 x 14.3 cm / 9" x 15.8" x 5.6"
<b>ASSEMBLED WEIGHT</b>	147.1 kg / 324.4 lbs.
<b>STEP-ON HEIGHT</b>	26.7 cm / 10.5"
<b>TOP-DOWN LEVELERS</b>	No
<b>SHIPPING WEIGHT</b>	164.1 kg / 361.8 lbs.
<b>RESISTANCE LEVELS</b>	30
<b>RESISTANCE RANGE</b>	24–160 SPM