



## Performance ClimbMill

### LED CONSOLE

C-PS-LED

Give members an exceptional climb with a premium ClimbMill engineered for unmatched security and durability. Control Zone stops the stairs instantly if anything pushes against rotation, and robust components withstand hard use. A range of refined design features makes every workout more comfortable and service quicker and easier than ever.



Virtually anyone can step up to our LED Console and enjoy the easy navigation of the interface. Complete, easy-to-read workout feedback helps members gauge performance at a glance.

| CONSOLE                          |  |
|----------------------------------|--|
| DISPLAY                          | Large number LED with message center   |
| WORKOUTS                         | Go, manual, interval training, fat burn, rolling hills, target heart rate, glute training†, fitness tests<br><br>†Some of these programs may not be available on this frame. |
| IFIT ON-DEMAND WORKOUTS          | No   |
| LANGUAGES                        | English, German, French, Italian, Spanish, Dutch, Portuguese, Swedish, Finnish, Turkish, Danish, Polish  |
| FAN                              | No   |
| IPTV                             | No   |
| WIFI                             | Optional; included with Asset Management and Workout Tracking Network App  |
| BLUETOOTH                        | No   |
| ANT+                             | No   |
| RFID WIRELESS LOGIN              | Optional   |
| CONNECTS TO APPLE WATCH          | No   |
| MADE FOR IPHONE, IPAD, IPOD      | No   |
| CONNECTS TO SAMSUNG GALAXY WATCH | No   |
| USB PORT                         | Yes; device charging, software updates   |
| WIRELESS CHARGING (QI)           | No   |

| CSAFE READY             | Yes   |
|-------------------------|---|
| AUTO WAKE-UP            | No  |
| FRAME                   |   |
| TOP-DOWN LEVELERS       | Yes   |
| RESISTANCE RANGE        | 24–162 SPM  |
| RESISTANCE LEVELS       | 25  |
| DRIVE SYSTEM            | Clutched ECB with motorcycle-grade, sealed drive chain and belt |
| HANDLEBAR DESIGN        | Perimeter   |
| LOCKING STAIRCASE       | Yes   |
| MAXIMUM USER WEIGHT     | 182 kg / 400 lbs.   |
| POWER REQUIREMENTS      | 100–240 V — 50/60Hz AC  |
| MINIMUM USER WEIGHT     | 45 kg / 99 lbs.   |
| STEP DIMENSIONS         | 25.4 x 46 x 20.3 cm / 10" x 18" x 8"                            |
| SERVICE CASTER          | Yes   |
| ASSEMBLED WEIGHT        | 188.8 kg / 416.2 lbs.   |
| SHIPPING WEIGHT         | 209.8 kg / 462.5 lbs.   |
| ASSEMBLED DIMENSIONS    | 182.5 x 102.4 x 219.1 cm / 71.9" x 40.3" x 86.3"                |
| CONTROL ZONE            | Yes   |
| CONTACT & TELEMETRIC HR | Yes   |
| ETHERNET CONNECTIVITY   | Yes   |
| STEP-ON HEIGHT          | 25.4 cm / 10"   |